




EHD



The Extra High Door (EHD) is used in industrial settings at large door openings. EHD units are manufactured in single increments that can be provided up to 30 ft. wide. The EHD has top and bottom access panels to replace or service motors or blowers without lowering entire unit or bottom half of unit. All industrial units are direct drive, which avoids misalignment of couplers and outboard bearings and eliminates periodic belt replacement. The motor/blower plate comes out as an entire piece and all parts on the outside of the unit are constructed of stainless steel.



OPTIONS

HEATING

Electric.	pg 181
Hot Water.	pg 186
Steam	pg 186
Indirect Gas.	pg 189
Direct Gas.	pg 195

AT A GLANCE

Single Incremental Widths

4' to 20'

Max Installation Height

22'

Heavy Duty Motors

5 HP

KEY DESIGN FEATURES

- Outer cabinet constructed of 18-gauge 304 stainless steel with #3 finish
- 5 HP TEAO (Totally Enclosed Air Over) direct-drive single-speed motor(s)
- High-efficiency discharge plenum with adjustable air foil vane (+/-20°)
- Top and bottom access panels for servicing and removal of motor-blower assembly
- NEMA 12 control panel with factory installed magnetic motor starter, overload relays, and control transformer

RECOMMENDED CONTROLS

- Activation by 24V magnetic door switch
- Toggle disconnect switch
- Hand/Off/Auto selector switch

