CED-E | PERFORMANCE

OED E	l Performanc	
	I Dartarmane	a lanic

MODEL	Nozzle Width (in.)	Max. FPM at Nozzle	Avg. Outlet Velocity (FPM)	Airflow Rate (CFM)	Outlet Velocity Uniformity	Power Rating (kW)	Number of Motors	Motor HP	Heater kW	Temp. Rise (°F)	Weight (lbs)
CED-1-36E	36	5560	1074	795	87%	0.24	1	1/2	10	40	88
CED-1-42E	42	5305	1030	886	96%	0.24	1	1/2	10	36	95
CED-1-48E	48	4628	987	967	94%	0.25	1	1/2	10	33	102
CED-1-60E	60	5096	822	1011	89%	0.25	1	1/2	10	32	113
CED-2-72E	72	5560	1074	1590	87%	0.48	2	1/2	20	40	172
CED-2-84E	84	5305	1030	1772	96%	0.48	2	1/2	20	36	192
CED-2-96E	96	4628	987	1934	94%	0.50	2	1/2	20	33	206
CED-3-108E	108	5560	1074	2385	87%	0.72	3	1/2	30	40	244
CED-3-120E	118	5028	1039	2557	87%	0.73	3	1/2	30	37	272
CED-3-132E	133	4996	960	2601	87%	0.73	3	1/2	30	37	285
CED-4-144E	145	5560	1074	3180	87%	0.96	4	1/2	40	40	344
CED-4-156E	157	5300	1051	3362	87%	0.96	4	1/2	40	38	362
CED-4-168E	169	5305	1030	3554	96%	0.96	4	1/2	40	36	380

For a unit over 14 feet long, or a non-standard electric heater kW, consult factory.

CED-E | Velocity Projection

Distance From Nozzle	40"	80"	120"	160"	
CED1-36E Core Velocity (fpm)	859	675	542	437	

CED-E | Sound Levels

Measured 10 ft. from unit in a free field based on a 1 motor unit 53 dBA

CED-E | Single Phase Motor Options

Voltages available	120	208/230	480	Note:
Amp draw per motor	2.5	1.4	0.7	575v is transformed down to 120v





Heating elements are mounted inside the plenum, on the discharge side of the blowers. Here, heat won't affect motor life and the heaters are protected from dust that would accumulate on them if they were mounted on the air intake.

The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only. Rated data shown are based on tests of units with heating elements present but not in use.