



TFD-HW



TFD-ST

▶ TFD-HW/ST | PERFORMANCE

TFD-HW/ST | Heating Information Table

MODEL	Hot Water		Steam		Weight (lbs)
	mbtu /Hour	Temp. Rise (°F)	mbtu /Hour	Temp. Rise (°F)	
TFD-1-36HW/ST	131	34	136	35	165
TFD-1-48HW/ST	132	34	133	34	182
TFD-1-60HW/ST	141	35	140	35	212
TFD-2-72HW/ST	261	33	263	34	335
TFD-2-84HW/ST	269	34	270	34	346
TFD-2-96HW/ST	270	34	270	34	360
TFD-2-108HW/ST	267	34	266	34	382
TFD-3-108HW/ST	403	34	395	34	500
TFD-3-120HW/ST	408	35	393	33	516
TFD-3-132HW/ST	400	34	414	35	526
TFD-4-144HW/ST	529	34	551	35	665
TFD-4-156HW/ST	530	34	554	35	681
TFD-4-168HW/ST	530	34	554	35	692



INFO

For additional TFD-HW/ST performance information, reference performance table on page 148.

▶ TFD & TFD-HW/ST MECHANICAL DETAILS

TFD & TFD-HW/ST | Mechanical Information Table

MODEL	Overall Width (in.)	Nozzle Width (in.)	Mounting Width Rear and Top (in.)
TFD-1-36 (HW/ST)	39	36	37.5
TFD-1-48 (HW/ST)	51	48	49.5
TFD-1-60 (HW/ST)	63	60	61.5
TFD-2-72 (HW/ST)	75.07	72.07	73.57
TFD-2-84 (HW/ST)	87.07	84.07	85.57
TFD-2-96 (HW/ST)	99.07	96.07	97.57
TFD-2-108 (HW/ST)	111.07	108.07	109.57
TFD-3-108 (HW/ST)	111.15	108.15	109.65
TFD-3-120 (HW/ST)	123.15	120.15	121.65
TFD-3-132 (HW/ST)	135.15	132.15	133.65
TFD-4-144 (HW/ST)	147.22	144.22	145.72
TFD-4-156 (HW/ST)	159.22	156.22	157.72
TFD-4-168 (HW/ST)	171.22	168.22	169.72