



ECC-HW



ECC-ST

v4.2.0

# ECC-HW/ST



ABOVE CEILING

The ECC model air curtain is specifically designed to be dropped into the ceiling above customer entryways where a standard air curtain cannot be exposed.

## OPTIONS

### HEATING

- Hot Water . . . . .ECC-HW
- Steam . . . . .ECC-ST
- Unheated . . . . .pg 53
- Electric. . . . .pg 53

### FILTER

½" cleanable

### GRILLE COLOR

The white grille is standard with this model.  
Consult factory for custom color or metal.



## AT A GLANCE

Single Incremental Widths

3' to 12'

Max Installation Height

14'

Heavy Duty Motors

¾ HP

### KEY DESIGN FEATURES

- White decorative intake grille with hinged access panel (consult factory for custom finishes)
- ¾ HP EC (Electronically Commutated) direct-drive motor(s) with 2:1 speed turndown ratio and instantaneous startup
- High-efficiency discharge plenum with adjustable air foil vane (+/-20°)
- Coil made to AHRI Standard 410
- Hot water coil comprised of galvanized steel casing, 5/8" copper tube, aluminum fins, and same end supply/return connections
- Leak tested at 450 psi
- Custom coil selections available (consult factory)

### RECOMMENDED CONTROLS & ACCESSORIES

- Activation by 24V magnetic door switch
- Toggle disconnect switch
- SmartTouch controller
- Hot water or steam control valve with actuator
- Filter (washable)