



ECC



ECC-E

3.1.2

ECC

ABOVE CEILING



The ECC model air curtain is specifically designed to be dropped into the ceiling above customer entryways where a standard air curtain cannot be exposed.

OPTIONS

HEATING


- ElectricECC-E
- Hot Waterpg 23
- Steampg 23

FILTER

½" cleanable

GRILLE COLOR

The white grille is standard with this model. Consult factory for custom color or metal.



AT A GLANCE

Single Incremental Widths

3' to 12'

Max Installation Height

14'

Heavy Duty Motors

¾ HP


KEY DESIGN FEATURES

- Heavy duty ¾ HP EC motors. 1650 rpm on high speed.
- 2:1 turndown ratio when used with optional speed dial.
- Galvanized fans.
- White powder coated decorative intake grille
- High efficiency discharge plenum ensures that air being discharged fills the entire width and height of the opening. This also lowers the unit's operational sound level.
- Directional air foil vane factory set to facilitate deflection of air stream +/-20 degrees.
- Includes control panel

RECOMMENDED CONTROLS

- Variable speed dial
- Thermostat, if electrically heated (Model ECC-E)
- Magnetic Door Switch for activation
- Time Delay Relay

MEASURING EFFICIENCY



Data based on ¾ HP @ 120V