MOTION SENSOR AIR CURTAIN ACTIVATION Technical Data




PRODUCT IMAGE



FEATURES AND KEY PRODUCT INFORMATION

- ▶ Microwave motion detector for activation of air curtain.
- ► Capable of detecting presence of pedestrians, forklifts and other traffic approaching a door.
- Unidirectional & bidirectional detection capable of detecting (or ignoring) depending on direction of traffic.
- ► Two planar antenna included for selection of narrow or wide detection area.
- ➤ Can be mounted as high as 15 feet above door (consult Powered Aire if higher height is required).
- ► Easy to install and set-up without external proprietary devices.
- Wire harness included for easy set up and tie in to air curtain activation.



ALTERNATE VIEWS



APPLICATION NOTES

Adjustable sensitivity and time-delay settings

Rain cover available (not included)

Visible LEDs To Verify Activation In Normal Operating Mode

Must be mounted in area where air curtain does not block detection field


FC CE IC

QUESTIONS & TECHNICAL SUPPORT AVAILABLE. CONTACT US DIRECTLY:

MOTION SENSOR AIR CURTAIN ACTIVATION Technical Data



PRODUCT DRAWING



Characteristics	
Frequency	24.125 GHz ± 50 MHz (K-Band)
Detection Method	Doppler Shift Radar
Detection Pattern	Selectable, wide or narrow
Detection Angle	Adjustable, 21° to 90°, ±25° Left/Right
Directionality	Switch Selectable, Unidirectional or Bidirectional
Range	Adjustable (range pot.)
Max. Mounting Height	15′ (4.5m)
Power Requirements	12V to 24V AC or DC ± 10%
Power Consumption	3.5W Maximum
Output Contact	Form C, Rated at 1 Amp
Output Power	5mW Typical, 2mW Minimum
Hold Time	Adjustable, 1.5 to 5 Seconds
Mounting	Flush (optional universal mounting bracket available)
Temperature	-22°F to 158°F (-30°C to 70°C)
Color	Black
Weight	<1 lb. (0.45kg)
Size	6 1/2"W x 1 7/8"H x 2 3/4"D 16.5cmW x 4.8cmH x 7cmD