

DECORATOR SWITCHES

For remote mounting, Decorator switches promote an attractive installation for Powered Aire's exposed or above the ceiling models



Single Gang

Double Gang



Triple Gang

MULTIPLE COMBINATIONS AVAILABLE



Individual Switch Options/Functions

(any combination of switches can be used on double or triple controls)

1. High/Off/Low
2. High/Low
3. High/Medium/Low
4. Hand/Off/Auto
5. On/Off

FEATURES AND KEY PRODUCT INFORMATION

- ▶ Decorator switches enable complete air curtain control but blend in/match with common activation switches. Low profile switches are ideal for commercial and retail settings.
- ▶ Available in a single, double, or triple configurations.
- ▶ Switches control air curtain fan and heating functions.
- ▶ Decorator switches combine style with durability. The switches are available in single pole, double pole and three-way.

Standards/Listings/Certifications

ANSI	C-73
CSA C22.2 No.111:	File# 152105
NEMA	WD-1 & WD-6
NOM	057
UL Standard	UL20

FOR TECHNICAL SUPPORT OR QUESTIONS, CONTACT US DIRECTLY:

Phone Support
1-888-321-Aire (2473)

Email Support & Service
CustomerService@PoweredAire.com


Sales Questions
Sales@PoweredAire.com

DECORATOR SWITCHES




Technical Data

PRODUCT DRAWINGS

Common Wiring Configurations



Common Configurations



Electrical Specifications

Amperage	15 Amp
Dielectric Voltage	Withstands 1500V for 1 minute
Endurance	50,000 cycles minimum
Grounding	Self-Grounding
Overload UL20 Test	100 cycls. of OL @ 4.8 times rated current
Temperature Rise	Maximum 30 degrees C rise
Voltage	24-277 VAC

Environmental Specifications

Flammability	Rated V-2 per UL 94
Operating Temp.	-40°C to 65°C

Material Specifications

Actuator Material	Thermoplastic
Body Material:	Thermoplastic
Color	White
Strap Material:	Steel

Mechanical Specifications

Product ID:	Stamped on Strap
Terminal Accom.	14-#10 AWG back wired; #14-#12 AWG side wired
Terminal ID	Brass-Hot Black-Hot White-Neutral Green-Gnd
Termination	Back or Side Wire
Torque Range	12-14 inch pounds

Complete List of Decorator Switches

Available Parts	Description
5865-2W	Single pole, double throw, center off Used for HOL and HOA switches
5686-2W	Double pole, double throw, center off
5691-2W	Single pole, single throw. Used for On/Off switches
5693-2W	Single pole, double throw. Used for HL switches. No center off
5641-W	Combo Switch, One three-way, 1 single pole
80301-SW	Screwless wall plate for 1 switch
80309-SW	Screwless wall plate for 2 switches
80311-SW	Screwless wall plate for 3 switches

FOR TECHNICAL SUPPORT OR QUESTIONS, CONTACT US DIRECTLY:

Phone Support
1-888-321-Aire (2473)

Email Support & Service
CustomerService@PoweredAire.com

Sales Questions
Sales@PoweredAire.com