



CLD-HW



CLD-ST

3.3.0

CLD-HW/ST



LIGHT DUTY

ABOVE CEILING

The Chameleon is specifically designed to be dropped into the ceiling above customer entry ways where a standard air curtain cannot be exposed. Like the CED, the Chameleon also has the least objectionable airflow.

OPTIONS

HEATING

Hot WaterCLD-HW
SteamCLD-ST
Unheatedpg 45
Electricpg 45

FILTER

½" Cleanable

CUSTOM GRILLES

The white grille is standard with this model.
Consult factory for custom color or metal.



AT A GLANCE

Single Incremental Widths

3' to 12'

Max Installation Height

11'

Heavy Duty Motors

½ HP

KEY DESIGN FEATURES

- 18 gauge galvanized steel case installed above the ceiling.
- Heavy duty ½ HP motors. 1075 rpm each. 50/60 cycle. Dual speed.
- Galvanized fans.
- White powder coated decorative intake screen
- High efficiency discharge plenum ensures that air being discharged fills the entire width and height of the opening. This also lowers the unit's operational sound level.
- Directional air foil vane factory set to facilitate deflection of air stream +/-20 degrees.
- Made-to-order steam or hot water coil mounted to intake of air curtain. Coil consists of 5/8 in. O.D. copper tubes and aluminum fins. Coils certified to ARI standard 410
- Includes control panel

RECOMMENDED CONTROLS

- ON / OFF switch
- Magnetic door switch for activation
- Time delay relay

