




TSD-DG

The Direct Gas Fired model provides the most heat of any air curtain in the Powered Aire product line. With the Direct Fired air curtain, the intake air goes directly through the flame prior to being discharged. This air curtain will provide up to a 105 °F instant temperature rise at the threshold. Not only will this model prevent cold air from infiltrating the opening, it will help keep door hinges from freezing, keep the floor dry, help keep employees comfortable and promote safety and productivity. Certain codes apply; contact factory for details.

OPTIONS

HEATING

Unheated	pg 161
Hot Water / Steam	pg 167
Indirect Gas	pg 171
Electric.	consult factory



AT A GLANCE

Single Incremental Widths

8' to 16'

Max Installation Height

17'

Heavy Duty Motors

3 HP

KEY DESIGN FEATURES

- All weight bearing structural support is made of formed 11-gauge stainless steel and galvanized steel. Outer casing is constructed of 16-gauge stainless steel.
- Heavy duty 3 HP Total Enclosed Aire Over (TEAO) motors at 1160 rpm each, 50/60 cycle. Single speed.
- Galvanized fans.
- Air intake screen is perforated stainless steel.
- Access panels for inspection, cleaning or removal of motor blower assembly, without having to lower the unit.
- High efficiency discharge plenum with directional air foil vane factory set to facilitate deflection of air stream +/- 20°.
- Includes NEMA 12 control panel with magnetic motor starter, overload relays and control transformer.

RECOMMENDED CONTROLS

- Panel mounted HAND / OFF / AUTO switch
- Thermostat
- Magnetic Door Switch for activation

